

Sewing Pattern — Jacket 4296

Recommendations on fabric: leather / faux leather

You will also need: lining; one separable zipper; 2 zippers for pockets; shoulder pads.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm, lower edge of sleeves – 4 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



ATTENTION: Back part lining details are cut using main fabric pattern pieces excluding the neckline facings and lower facing of back part correspondingly.

CUTTING:

Main fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Central front part – 2 details
4. Side front part – 2 details
5. Yoke of front part — 2 details
6. Stand-up part of collar – 2 details
7. Upper sleeve part – 2 details
8. Lower sleeve part – 2 details
9. Back neckline facing – 1 detail
10. Buttonstand – 2 details
11. Back part facing — 1 detail
12. Front part facing — 2 details
13. Underlay piece - 2 details

Lining:

1. Central back part – 2 details
2. Central front part – 2 details
3. Side back part – 2 details
4. Side front part – 2 details
5. Upper sleeve part – 2 details
6. Lower sleeve part – 2 details
7. Big pocket bag — 2 details
8. Small pocket bag — 2 details

INSTRUCTIONS:

1. Sew darts on back part. Press depths towards center. Sew princess edges on back part. Press seam allowances towards center. Put decorative stitch at 0.5 cm off the seam. Sew center edge of back part. Press seam allowance apart.
2. Topstitch bias tape from fusing onto big pocket bag. Mark pocket location on front part. Specify the line of pocket opening. Cut the pocket opening through. Make cross slashes at 1-1.5 cm off the pocket end. Turn seam allowances of the pocket wrong side out through the given slit, straighten edges. Straighten out the end of pocket from the wrong side. Stitch lining with its right side to wrong side of zipper tape. Put the zipper under the edge of pocket opening so that zipper blade can not be seen. Sew zipper in, turning back the lining. Sew edges of lining.
3. Sew princess edges on front part. Press seam allowances towards center. Put decorative stitch at 0.5 cm off the seam. Stitch yoke to front part. Press seam allowance onto yoke and put decorative stitch at 0.5 cm off the seam.
4. Sew and press apart side and shoulder edges of the jacket.
5. Sew seam on lower part of sleeve. Press seam allowance to back part. Put decorative stitch at 0.5 cm. off the seam. Sew upper part of sleeve into lower. Slash seam allowances and press onto lower part. Put decorative stitch at 0.5 cm. off the seam. Sew sleeves into the jacket. Sew shoulder pads.
6. Sew outer stand-up part of collar into the neckline. Press apart the seam.
7. Sew in the zipper.
8. Sew seams on lining details, leaving a slit in left side seam. Sew in sleeves. Sew shoulder seams of buttonstands and of the facing. Press apart the seam. Stitch lining to buttonstands and facing. Sew together seams of lower facings. Press apart the seam. Stitch facings to lining. Sew inner stand-up part of collar into the neckline. Press seam allowance apart.
9. Put the buttonstand onto right side of front part with its right side downwards, pin together and overstretch along buttonstand and along stand-up part. Overstretch hem of the garment. Stitch lining to lower edge of sleeve. Fasten upper edge of lower facing to main fabric seams. Fix together allowances of stand-up parts connecting seams. Turn jacket out through the slit. Sew the slit.
10. Put two decorative parallel stitches along front band and along the hem at 0.2 and 0.5 cm off the edge. Put decorative stitch along stand collar.

TECHNICAL DRAWING:

