

Sewing Pattern — Lace body 5242

Recommendations on fabric: elastic jersey.

You will also need: one small button; bias binding; elastic lace; hook-and-eye tape.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

- 2. Back – 2 pieces
- 4. Front – 1 folded piece

Lace:

- 1. Back yoke - 2 pieces
- 3. Front yoke – 1 folded piece
- 5. Crotch facing – 2 pieces

INSTRUCTIONS:

1. Stitch the back yoke central seam leaving a fastening slit. Stitch the backcentre seam.
2. Stitch the shoulder seams of the yokes.
3. Cut the seam allowances of the back/front top edges away. Stitch bias binding to the wrong side of the garment, turn it round the edges to the right side and topstitch it. Use this method to finish the neckline and armholes.
4. Stitch the side seams. Cut the seam allowances away from the leg openings and finish them with the bias binding tape. Cut the seam allowances away from the outer crotch facing and finish it

with the bias binding also.

6. Press the inside leg seam allowances to the wrong side. Place the hook-and-eye tape under them and topstitch it stitching on the right side of the garment.

7. Make a loop on the right top edge of the slit, attach the button to the left side.

TECHNICAL DRAWING:

