

Sewing Pattern — Pyjamas/top 5235

Recommendations on fabric: light silk or cotton material (cambric).

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back – 1 folded piece
2. Bust pocket – 1 piece
3. Front – 2 pieces
4. Back facing - 1 folded piece
5. Belt – 1 folded piece
6. Sleeve – 2 pieces

INSTRUCTIONS:

1. Fold the top edge of the pocket to the right side and stitch the side edges. Turn it right side out. Press the seam allowances of the pocket to the wrong side according to the pattern. Topstitch the pocket top. Topstitch the pocket to the garment.
2. Stitch the side/shoulder/sleeve seams. Press them open.
3. Stitch the facing shoulder seams. Press the seams open.
4. With right sides together stitch the front facing to the garment. Cut the seam allowances and turn the edging inside out.
5. Stitch the sleeves to the garment.

6. Fold the sleeve hems and the garment hem inside and topstitch them.
7. Make up and topstitch the belt.

TECHNICAL DRAWING:

