

Sewing Pattern — Chemise 5234

Recommendations on fabric: natural or mixed silk (satin, atlas)

You will also need: elastic lace tape with scalloped edge

If you are planning to use non-transparent fabric, you don't need lining

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back - 1 folded piece
2. Cup – 2 pieces
3. Front - 1 folded piece
4. Strap – 2 pieces
5. Back facing - 1 folded piece

Elastic:

6. Trimming – 1 piece

INSTRUCTIONS:

1. Stitch the front/back darts.
2. Pin the lace tape to the cup top edges adjusting the edges. Press the lace making necessary shape. Make splits at the corners of the lace and stitch them as seams. Cut and neaten the seam allowance. Topstitch the lower edge of the lace to the cups. Cut the cups fabric under the lace leaving 1cm. allowance. Press this allowance to the cups. Stitch the lower edge of the lace to the cups with narrow zigzag stitch. Cut the extra fabric close to the seam.

3. Stitch the cup darts. Stitch the cups to the front piece.
4. Make up shoulder straps.
5. With right sides together place the back facing on the back top edge. Stitch sandwiching the shoulder straps between. Trim the seam allowance leaving 0,3 cm. Fold the facing to the wrong side, tack and press it.
6. Try the chemise on, check the length of the shoulder straps and stitch them to the top corners of the cups.
7. Measure the width of the hem. Cut piece of the lace tape according to this size, sew its side edges together. Stitch the lace to the hem face to face. Press the seam upwards and topstitch it to the garment on the skirt close to the seam.

TECHNICAL DRAWING:

