

Sewing Pattern — Shorts 5229

Recommendations on fabric: light silk or cotton.

You will also need: cambric; elastic tape.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

2. Front – 2 pieces
1. Back – 2 pieces

INSTRUCTIONS:

1. Stitch the side/inside leg seams. Press them open.
2. Turn one leg right side out and place it inside the other leg. Stitch the crotch seam leaving a slit in the seam above the along the marked waist foldline.
3. Fold the raw to edge of the garment for 0, 5 cm under and press it flat. Fold the waist integrated facing to the wrong side and topstitch it 0.1 cm above the lower folded edge. Make two rows of stitches according to the marks. Cut 3 piece of elastic to fit the waist, plus 2,5 cm. Thread these pieces of elastic through the casing. Overlap and stitch the elastic ends.
4. Fold the hem to the wrong side and topstitch it 0,1 cm above the foldline.

TECHNICAL DRAWING:

