

Sewing Pattern — Nightdress 5227

Recommendations on fabric: light cotton material (cambric).

You will also need: netted lace edging, 7 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front – 2 pieces
2. Back – 1 folded piece
3. Sleeve – 2 pieces
4. Skirt – 2 folded pieces
5. Binding bias – 1 piece

INSTRUCTIONS:

1. Stitch bust darts and press them downwards.
2. Neaten and stitch the skirt side edges, bodice side edges, shoulder/sleeve edges. Press the seams open.
3. Press the integrated facings to the right side of the garment front along the marked center front foldline. Fold the raw edges of the facings under, press them and tack to the garment.
4. Finish the neck edge with the binding bias.
5. Stitch the sleeves to the armholes.

6. With the center front lines matching put the right front piece on the left front piece and tack the overlapped lower edges. Gather the skirt top edge and stitch it to the bodice. Neaten the seam and press it upwards.
7. Neaten the skirt/sleeve hems and turn them to the wrong side. Press these flat. Place lace tape under the skirt and sleeves hems with finished edges shown, and topstitch these.
8. Make buttonholes in the right front piece, sew the buttons to the left front piece.

TECHNICAL DRAWING:

