

Sewing Pattern — Dress 5205

Recommendations on fabric: sheer jersey of 150 cm.

You will also need: fusing; zipper.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Middle front part – 1 piece
2. Right side front part – 1 piece
3. Left side front part – 1 piece
4. Middle back part – 1 piece
5. Right side back part – 1 piece
6. Left side back part – 1 piece
7. Panel – 2 pieces

Fusing: Neckline, armhole and front/back hem.

INSTRUCTIONS:

1. Apply the fusing straps to wrong side of neckline edge, edges of armholes and front/back hem.
2. Sew front/back relives.
3. Sew right side seam and left edge seam.

4. Press allowances of neckline and armholes to wrong side (do not strengthen them). Topstitch the dress along armholes and neckline with double stitch at 1 cm.
5. Sew the zipper along left side edges.
6. Sew left side edge. Fold zipper braid upper ends under and sew near armhole edge.
7. Sew side seams of panels. Sew the skirt to upper part of dress.
8. Press hem to wrong side and topstitch it with small zig zag.

TECHNICAL DRAWING:

