

Sewing Pattern — Dress 5199

Recommendations on fabric: satin of 150 cm width

You will also need: lace with small flounces along edgings; lace with frill edge; silk taffeta; organza; fusing; zipper; corsage braid of 0.75 cm width

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

- 1. Back middle part 2 pieces
- 2. Back side part 2 pieces
- 3. Front side part 2 pieces
- 4. Front central part 1 folded piece
- 5. Back panel 1 folded piece
- 6. Front panel 1 folded piece

Lace:

- 5. Back panel 1 folded piece
- 6. Front panel 1 folded piece

<u>ATTENTION:</u> cut panels without hem allowances and place them into fabric coinciding pattern lower edge with fabric flounces

Organza:

- 5. Back panel 1 folded piece
- 6. Front panel 1 folded piece



Taffeta:

- 1. Back middle part 2 pieces
- 2. Back side part 2 pieces
- 3. Front side part 2 pieces
- 4. Front central part 1 folded piece
- 5. Back panel 1 folded piece
- 6. Front panel 1 folded piece

Fusing:

- 1. Back front part 2 pieces
- 2. Back side part 2 pieces
- 3. Front side part 2 pieces
- 4. Front central part 1 folded piece

INSTRUCTIONS:

- 1. Sew back middle seam, back/front relieve seams. Sew fabric side seam.
- 2. Cut corsage braid into 5 equal parts. Sew part from dress upper edge to allowances of right side seam, relieve/middle back seams well as slit left edge.
- 3. Sew back middle seam, back/front relieve seams, right side seam of taffeta details. Lay taffeta upper part on satin upper part, right sides together, and overstitch along upper edges. Fold the taffeta and topstitch on seam allowance at 1-2 mm from stitch. Press upper part. Tack along side/lower edges.
- 4. Sew right side seam; sew left seam from the mark downwards (in all skirts). Insert skirts as following: satin skirt, lace skirt, organza skirt and the latest must be taffeta skirt. Tack skirts together along upper edge coinciding seams and middle lines.
- 5. Sew upper part to skirts right side together. Press the seam upwards.
- 6. Press closure allowance into wrong side. Sew the zipper with its teeth hidden folding braid downwards.
- 7. Sew hems of skirts so that all layers are with 1 cm clearance.



TECHNICAL DRAWING:

