

## Sewing Pattern — Dress 5192

Recommendations on fabric: soft sheer (suitable for dresses)  
fabric of 150 cm width.

You will also need: lining; 1 zipper.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Back part – 2 pieces
2. Front part – 1 folded piece
3. Front panel – 1 folded piece
4. Back panel – 2 pieces
5. Strap – 2 pieces

#### Fusing:

6. Back part – 2 pieces
7. Front part – 1 folded piece
8. Front panel – 1 folded piece
9. Back panel – 2 pieces

### **INSTRUCTIONS:**

1. Cut front panel and back panel diagonally.  
Let the dress hang during a day, and then mark new hem line.
2. Sew darts, press depths flat.
3. Sew side seams and sew the skirt to dress upper part.
4. Sew middle seam from lower edge to closure mark. Sew the zipper in.
5. Fold strap along the center, wrong side out, stitch along long edge, then turn right side out and

press. Tack front ends under front upper corners.

6. Sew fabric/lining dart and seams.

7. Fold fabric dress and lining right sides together. Fold allowance of back middle edge stopping 5 mm before zipper edge and pit it to neckline. Fold allowances of fabric closure into right side. Overstitch armholes and neckline catching front ends of straps. Fold lining into wrong side and sew to zipper braid and waistline seam allowance.

8. Try the dress, fit strap length and sew back ends to back upper corners.

9. Press the hem into wrong side and sew by hand. Sew lining hem 1.5 cm shorter than garment one.

**TECHNICAL DRAWING:**

