

Sewing Pattern — Dress 5172

Recommendations on fabric: crepe-satin of 150 cm width (for skirt); Flemish point of 90 cm width (for top).

You will also need: 1 zipper; 12 buttons.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Flemish point:

1. Upper middle front part – 2 folded pieces
2. Upper side front part – 4 pieces
3. Upper back part – 4 pieces
4. Sleeve – 4 pieces

Crepe-satin:

5. Middle back skirt – 2 pieces
6. Side back skirt – 2 pieces
7. Middle front skirt – 2 pieces
8. Side front skirt – 2 pieces
9. Pining for loops of 65 cm length and 3 cm width

INSTRUCTIONS:

1. Stitch darts into Flemish point details, stitch front relieves, side/shoulder seams and sleeve seams. Cut seam allowances to 0.75 cm, neaten them together and press towards the same direction. Press darts' depths toward middle line.
2. Make narrow roll of the piping, cut it into 5 cm pieces and make loops. Pin loops to inner edge of left outer back part; loops' tops lay on back part and loops' ends – on the edge allowance. Loop's size depends on button's diameter.

3. Lay outer/inner Flemish parts right sides together and stitch middle back edges and necklines. Cut seam allowances to 0.5 cm width and topstitch along middle back edges and neckline. Tack lower edges/necklines; do not fold edges under.
4. Lay sleeves in pairs, overstretch along lower edges and topstitch along edges. Tack open upper edges. Stitch sleeves in easing along sleeve caps. Cut sleeve allowances close to stitch and neaten them.
5. Stitch relieve/side/middle seams in skirts. Leave closure slit unstitched.
6. Stitch the skirt to the bodice, press seam allowances downward. Stitch the zipper with its teeth hidden folding braid's upper corners under.
7. Fold hem allowance into wrong side, fold under and topstitch.

TECHNICAL DRAWING:

