

## Sewing Pattern — Jacket 4190

Recommendations on fabric: natural or mixed suiting fabric.

You will also need: fusible interfacing; medium-weight lining; 6 buttons; shoulder pads, sleeve heads

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance: all seams - 1 cm, on hem of sleeve - 3 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### CUTTING:

The word “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

### Fabric:

1. Center back – cut 1
2. Inner side back – cut 2
3. Outer side back – cut 2
4. Center front – cut 2
5. Side front – cut 2
6. Yoke – cut 2
7. Inner front - cut 2
8. Upper sleeve – cut 2
9. Lower sleeve – cut 2

### Lining:

1. Center back – cut 1
2. Inner side back – cut 2
3. Outer side back – cut 2
4. Side front – cut 2
5. Upper sleeve – cut 2
5. Lower sleeve – cut 2

Interfacing:

Inner front, back neckline, sleeve hem

**INSTRUCTIONS:**

1. Apply interfacing.
2. Sew inner side backs to center back. Press seam allowances toward center. Sew outer side backs to inner side backs and press toward center. Sew side fronts to center fronts. Press seam allowances toward center.
3. Sew yoke to front and back. Press seam allowances toward yoke.
4. Sew side seams, press apart.
5. Sew upper and lower sleeve together, press apart elbow seam. Sew sleeve seam and press seam apart. Press hem of sleeve.
6. Make a gathering stitch on the sleeve cap for ease. Sew sleeves into armholes matching notches and adjusting ease. Sew in shoulder pads, and sleeve heads.
7. Sew seams on lining pieces. Sew in sleeves, leaving an opening in front right seam of sleeve for turning. Sew inner front to lining. Pin main garment and lining, right sides together, and sew along front stand, neckline and hem. Sew lining to hem of sleeve. Turn jacket, right side out, through the opening in the sleeve. Slipstitch opening closed.
8. Make buttonholes on right front and sew decorative buttons. Sew buttons on left front.

**TECHNICAL DRAWING:**

