

Sewing Pattern — Blouse 5154

Recommendations on fabric: silk of 150 cm width.

You will also need: fusing; 3 buttons; elastic braid of 50 cm length

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Middle front part – 2 pieces
2. Side front part – 2 pieces
3. Middle back part – 2 pieces
4. Side back part – 2 pieces
5. Front sleeve – 2 pieces
6. Back sleeve – 2 pieces
7. Front band – 2 pieces
8. Collar – 2 folded pieces
9. Coulisse – 1 piece
10. Sleeve coulisse – 2 pieces
11. Back neckline facing – 1 folded piece

Fusing: front band, outer collar, back neckline facing

INSTRUCTIONS:

1. Cut elastic braid into 4 pieces: 2 pieces of 15 cm length for sides and 2 pieces of 10 cm length for sleeves.
2. Stitch middle back seam and back relieves.

3. Stitch front relieves.
4. Stitch front/back sleeves to front/back parts correspondingly (right sides together).
5. Lay front part on back part. Stitch the coulisse to wrong side. Stitch elastic braids, fix at one end. Pull another end till necessary length and fix, too.
6. Stitch sleeve lower edge and side edge with one seam.
7. Stitch the coulisse to wrong side of front/back side parts. Stitch the elastic braid in the same way as to sleeves.
8. Stitch and process the collar along outer contour and tack long open edges into neckline. Stitch back neckline facing to front bands. Lay front bands and facing on the garment right sides together and overstitch along edgings, lapels and neckline catching the collar.
9. Turn front bands and facing wrong side out, tack, press. Sew facing's inner edges to seam allowances.
10. Neaten garment/sleeve hems, fold into wrong side, and then sew by hand.
12. Make buttonholes into right front edgings, sew buttons on left one.

TECHNICAL DRAWING:

