

Sewing Pattern — Dress 5136

Recommendations on fabric: soft knit fabric.

You will also need: 2 buttons, fusing.

Seam allowances are provided if the pattern has double contour.

Seam allowances are NOT included if the pattern has single contour and need to be added when laying out and cutting details.

Seam allowance 1 cm on all edges.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count double and symmetrical details.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Fabric:

1. back part – 1 folded piece
2. front part – 1 folded piece
3. front panel – 1 folded piece
4. back panel – 1 folded piece
5. string – 2 folded pieces
6. front neckline facing – 1 piece
7. back neckline facing – 1 piece
8. armhole facing – 2 pieces

Fusing: strings, facings.

INSTRUCTIONS:

1. apply the fusing to wrong side of inner parts of strings and facing details.
2. sew front and back parts along side edges. press allowances apart.
3. apply facing to neckline and armhole edges, right sides together, then sew. turn facings into wrong side, turn longwise edges under, and then topstitch close to the edge.
4. fold stripes right sides together, insert back shoulder edges and stitch along. overstretch stripe figure edges. turn stripes right side out, fold free lengthwise edges and make decorative stitch along stripe's edge.
5. fold front part short edges, and topstitch.
6. sew panels along side edges, press allowances apart.
7. sew lower edges of front and back parts to panel upper edges, press allowances upwards, then topstitch close to the edge.
8. press the hem under, then sew.
9. make strap loops, sew buttons on front short parts.



TECHNICAL DRAWING:

