

Sewing Pattern — Dress 5133

Recommended fabric: mixed linen of 150 cm width.

If the pattern has a double line around it, the seam allowances are included.

Seam allowance: 3 cm on hem; 1 cm on all other seams.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

(all pieces are cut on bias)

1. Back – cut 2
2. Front– cut 2
3. Bias binding for back/front facing - 1 piece (102 cm length, 3.5 cm width (including allowances)
4. Bias binding for armholes - 2 pieces (of 56 cm length, 3.5 cm width (including allowances)
5. Shoulder ties – 4 pieces (33 cm length, 4.5 cm width)

INSTRUCTIONS:

1. Sew front darts, press toward hem.
2. Sew center front seam to notch mark. Sew center back seam. Press seams apart.
3. Sew side seams. Press seams apart.
4. Fold bias strips along the center, wrong sides together, press long edges inside, so that they meet in the middle of strips. Baste bias strips to neckline/armholes fold lines, right sides together,

then sew short ends together. Turn strips onto wrong side and baste in place.

5. Topstitch strips on the right side along joining seam.

6. Sew ties right sides together, along center edge. Pin ties right side together. Sew contour, leaving an opening for turning. Turn right side out and press. Sew opening closed.

7. Let the dress hang 24 hours before hemming. Adjust hem line and serge lower edge and slit edge.

8. Press slit allowance and hem allowance onto wrong side.

9. Topstitch slit seam allowance and the hem on right side at 1.5 cm.

10. Tie a tie around each shoulder seam.

TECHNICAL DRAWING:

