

## Sewing Pattern — Jacket 4187

Recommendations on fabric: natural / mixed costume fabric

You will also need: fusing; 3 buttons; lining; shoulder pads; sleeve heads

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: vce seams 1 cm, on hem of the garment and of sleeve 3 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Main fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Central right front part – 1 detail
5. Central left front part – 1 detail
6. Right buttonstand– 1 detail
7. Left buttonstand– 1 detail
8. Flap – 1 detail
9. Upper sleeve part – 2 details
10. Lower sleeve part – 2 details
11. Back neckline facing – 1 detail

#### Lining:

1. Side back part – 2 details
2. Side front part – 2 details
3. Upper sleeve part – 2 details
4. Lower sleeve part – 2 details
5. Central back part – 2 details
6. Central front part – 2 details

**ATTENTION:** front part and back part lining details are cut according to main fabric patterns except for the width of buttonstands and back part neckline facing correspondingly.

Fusing: flap, buttonstand, back part neckline facing, central front part

### **INSTRUCTIONS:**

1. Apply fusing to flap, buttonstands, back neckline facing, central front part, edge of the armhole on front part and on back part.
2. Mark darts on front part and on back part. Sew and press darts on back part towards center. Sew darts on front part, slash away depth of dart. Press dart towards center of the detail and topstitch on 0.5 cm off the seam.
3. Sew relieve seams on back part and on front part, press seam allowances towards center and topstitch on 0.5 cm off the seam. Sew middle edge of back part, press seam onto left side.
4. Sew and press apart shoulder and side edges.
5. Fold flap detail right sides together and overstitch short edges. Turn onto right side, press, serge unsewn edge, put decorative stitch along the perimeter. Topstitch flap onto right front part according to markers.
6. Stitch back neckline facing to buttonstands, press seam allowances apart.
7. Fold buttonstands with garment and overstitch buttonstands edges and the neckline with one seam. Slash seam allowances in corners, slash on rounded parts, turn garment onto right side, press. Press hem of the garment.
8. Sew and press apart elbow edge of sleeve. Press hem of sleeve. Sew and press apart front edge of sleeve.
9. Sew sleeves into armholes according to notches. Sew in shoulder pads and sleeve heads.
10. Sew seams on lining details and sew in sleeves, leaving a slit in front right seam of sleeve.
11. Stitch lining to inner buttonstands edges and back part neckline facing.
12. Stitch lining to hem of jacket and of sleeve. Turn jacket through the slit in sleeve. Sew slit in sleeve.
13. Put decorative stitch along buttonstand, neckline and hem of jacket.
14. Serge buttonholes on right front part. Sew buttons on left front part.

### **TECHNICAL DRAWING:**

