

Sewing Pattern — Skirt 5121

Recommendations on fabric: light-weight skirt fabric.

You will also need: lining, fusible interfacing, skirt zipper, hook and eye.

If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowances: All seams 1 cm, 2 cm for hem

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as pleats etc. from the pattern onto your fabric.)

Fabric:

1. Middle front - cut 1 on fold
2. Middle back - cut 2
3. Front side - cut 2
4. Back side - cut 2
5. Cut a length of bias tape for facing the top edge of the skirt

Lining:

1. Middle front - cut 1 on fold
2. Middle back - cut 2
3. Front side - cut 2
4. Back side - cut 2
5. Interfacing: apply fusible interfacing to seam allowances of back lower slit.

INSTRUCTIONS:

1. Apply fusible interfacing to seam allowances of back lower slit.
2. Sew back middle seam between marker for zipper and marker for lower slit. Press apart seam allowances. Press seam allowances along edges of slit onto wrong side.
3. Sew in zipper according to zipper instructions.
4. Sew back sides to middle back and front sides to middle front. Sew front section to back section. Press seams open.
5. Sew seams of lining just like fabric instructions. Put lining inside skirt, wrong sides together, baste to top edge of the skirt, slip-stitch zipper opening in lining to tape of zipper.
6. Trim seam allowance along top edge of the skirt to 8 mm. Stay stitch upper edge of the skirt.
7. Fold bias tape in half lengthwise, wrong sides together, and press. Open the tape and turn one longer edge of bias tape to pressed fold and press. Turn the other longer edge of bias tape towards fold, not reaching it by 2 mm and press. Fold the bias tape along the pressed fold again. Insert upper edge of the skirt between the halves of bias tape, leveling the edge with pressed fold of bias tape, the wider part lies on the lining. Pin outer half of bias tape, turn inside ends of bias tape, sew edges, baste the bias tape and topstitch into edge. Sew hook and eye to ends of facing just above zipper.
8. Press seam allowance on hem of the skirt onto wrong side and sew by hand. Sew seam allowances along edges of lower slit to seam allowances of the slit. Turn and sew the hem of lining inside so that the lining is 2 cm shorter than the skirt.

TECHNICAL DRAWING:



