

Sewing Pattern — Blouse 4185

Recommendations on fabric: natural / mixed blouse fabric (silk, viscose)

You will also need: fusing, 5 buttons, elastic braid of 0.7 cm wide (approximate length is mentioned on sleeve pattern)

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: on hem of the garment – 1.5 cm, on hem of sleeve – 2 cm, all other seams – 1 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central back part - 2 details
2. Side back part - 2 details
3. Front part - 2 details
4. Side front part - 2 details
5. Sleeve – 2 details
6. Collar – 2 details
7. Back neckline facing – 1 detail
8. Buttonstand – 2 details

Fusing:

1. Buttonstand – 2 details
2. Back neckline facing – 1 detail

INSTRUCTIONS:

1. Apply fusing to buttonstands and back neckline facing.
2. Make plaits on collar. Fold collar in half lengthwise wrong sides together. Fix collars together.
3. Sew relieve edges on front part. Press seams to central part and serge.
4. Sew darts on back part. Press depths towards center. Sew relieve edges and middle edge of back part. Press the seam towards center and serge. Press middle seam onto left side and serge.
5. Sew shoulder and side edges. Press seams to back part and serge.

6. Stitch back part facing to buttonstands. Press seams apart. Serge outer edge of buttonstands and facing.
7. Sew collar into the neckline, inserting it between main garment and facing, oversteitching buttonstand at the same time. Turn buttonstand corner inside and undersew by hand to relieve seams of front part.
8. Straighten collar onto right side and press. Fasten the facing with hand stitches near middle seam of back part and near shoulder seams. Put decorative stitch along buttonstand.
9. Sew, press and serge edges of sleeves. Turn hem of sleeve inside twice at 1 cm. and press. Insert elastic braid between notches and tack with cross stitches. Topstitch hem of sleeve. Sew sleeve into armhole. Serge and press.
10. Serge hem of the garment, press onto wrong side and topstitch.
11. Serge buttonholes on right front part, sew buttons on left front part.

TECHNICAL DRAWING:

