

Sewing Pattern — Jacket 5104

Recommendations on fabric: artificial suede of 150 cm width

You will also need: lining; fusing; 4 flat buttons; shoulder pads; polyester batting.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Front part - 2 details
2. Middle part of front part - 2 details
3. Middle part of back part - 1 folded detail
4. Side back part - 2 details
5. Upper sleeve part - 2 details
6. Elbow part of sleeve - 2 details
7. Collar - 2 details со сгибом
8. Buttonstand - 2 details
9. Back neckline facing - 1 folded detail
10. Bag of pocket - 2 details

Lining:

1. Front part - except for the width of buttonstands, connect parts of paper pattern of front part;
2. Back part - except for the width of neckline facing and with the plait along center line of 2 cm wide for loose fit;
3. Upper sleeve part - 2 details
4. Elbow part of sleeve - 2 details
5. Bag of pocket - 2 details

Fusing: front part details, buttonstands, back neckline facing, collar and pockets; on sleeve details – one-piece facings (lapels). Apply fusing also to hem seam allowances of jacket's details

INSTRUCTIONS:

1. Stitch upper edge of middle part of each front part to front part. Sew a dart, leaving pocket opening unsewn.
2. Fold both pocket bags of each pocket with opening seam allowances from wrong side of front part right sides together and pin, pin lining bag to front allowance of pocket opening.
3. Stitch main fabric bag exactly along the marked seam line, a pocket bag from lining – leaving 0,75 cm to seam marked line. Turn bags to the front and sew.
4. Sew relieve seams of back part, side and shoulder seams. Put stitches on buttonstand of right front part on four sides of each buttonhole marking by pprox. 2 mm, underlaying a cloth ossuede from wrong side. Cut buttonholes.
5. Stitch back part neckline facing to buttonstands. Fold buttonstands and facing with jacket right sides together and pin to edges of buttonstands and lapels, buttonstands lapels on corners must be a little wider than front part lapels upwards. Stitch buttonstands to buttonstands and lapels edges up to cross marker (leave buttonstands lying on front parts right side to right side). Stitch collar clearly on outer contour, top collar must be a little wider than lower one. Put collar between buttonstands, facing and jacket. Sew lower collar into front parts neckline. Slash front parts in corners to the stitch. Sew longitudinal edge of lower collar into the jacket neckline. Sew upper collar into the buttonstands and facings neckline, slash seam allowances in buttonstands corners. Cut seam allowances of top and lower collars connecting seam to 0,75 cm, lay on both of the seam. Turn buttonstands onto wrong side. Pin top and lower of collars connecting seams on back part section. Turn facing upwards and sew connecting seam allowances close to the seam. Press seam allowance of jacket hem onto wrong side, but do not sew yet.
6. Sew sleeves seams. Turn seam allowances on sleeves hem onto wrong side and press.
7. Sew sleeves in, gathering slightly on rounded parts. Sew a tape of polyester batting of 4 cm wide under seam allowances of each sleeve connecting seam on rounded part section. Sew shoulder pads. Make a plait on lining of back part for loose fit and fasten it under neckline cut and on some cm above turn line of hem of the garment. Sew darts on details of lining. Sew details of lining similar to main garment, leaving a section near 20 cm of elbow seam of one of the sleeve unsewn. Insert lining into main garment right sides together, leveling on back part central line and shoulder seams. Overstitch main garment with lining on buttonstands and neckline. Stitch lining to hem of sleeves. Make a lapping plait along the edge of the garment and stitch lining to edge of hem. Turn garment through unsewn section of sleeve, sew this section.
8. Stitch right front part отстрочить along edge of buttonstand according to markers.

TECHNICAL DRAWING:

