

Sewing Pattern — Dress 4184

Recommendations on fabric: fabric suitable for dresses

You will also need: blind zipper, fusing, elastic band, lining

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: on hem - 2 cm, other seams - 1.0 cm.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central back part - 2 details
2. Side back part - 2 details
3. Central front part – 1 detail
4. Side front part - 2 details
5. Collar — 2 details
6. Sleeve - 2 details
7. Facing neckline – 1 detail

Lining:

1. Sleeve — 2 details

Fusing:

top collar, neckline facing

INSTRUCTIONS:

1. Apply fusing to details.
2. Sew relieve seams on back part. Press seam towards center and serge.
3. Apply fusing to the vent on both details of lower back parts. Mark the middle seam on right side (vent fold line). Sew middle edge of back part till vent's angle. Slash angle allowance of vent seam.

- Serge middle seam of back part and seam allowances of vent separately. Press seam allowances of middle seam on left side. Press right side of vent on 1 cm onto wrong side and topstitch. Press seam allowances of vent to left side seam and topstitch.
4. Overstitch the neckline of front part with facing. Slash seam. Turn details out and press.
 5. Sew relief edges of front part. Slash seam at top notch. Press seam allowance towards center of front part and serge.
 6. Sew shoulder seams and right side edge, press seam onto back part and serge. Serge left side edge separately and sew, leaving a slit between notches. Press seam apart, pressing a slit for zipper. Sew in blind zipper.
 7. Fold collar details right sides together and overstitch ends and outer edge of collar. Start and finish the stitch exactly near marked line of the seam to sew in collar. Turn ready collar out, straighten angles and press. Sew in outer edge of collar in the neckline. Press seam on collar. Turn open inner edge of collar and topstitch into the seam.
 8. Fold sleeve with lining right sides together and overstitch along the lower edge. Stitch between notches with the elastic band. Turn lining and fix it to sleeve along sleeve cap. Sew in sleeves into armholes, aligning notches. Press seam towards front part and back part and serge.
 9. Cut bias tape of 4 cm wide and length equal to the length of lower part of sleeve + 6 cm. Fold bias tape in half lengthwise wrong sides together and press. Fold the bias tape with edge of the armhole from the right side, leaving tails, and overstitch. Turn bias onto wrong side, slash seams and topstitch along the fold on main detail. Press the seam.
 10. Serge seam allowance of garment hem, press onto wrong side and topstitch.
 11. Dress is supposed to be worn with a belt.

TECHNICAL DRAWING:

