

## Sewing Pattern — Blouse 5064

Recommendations on fabric: Georgette crepe of 140 cm width

You will also need: elastic of 3 mm width; 3 small buttons  
If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: hem - 4 cm, all other seams - 1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

### **Fabric:**

1. Front– cut 2
2. Back – cut 2
3. Sleeve flounce – cut 2
4. Sleeve – cut 2

\*Additionally: bias tape 4.5 cm wide to finish neckline edge.

### **INSTRUCTIONS:**

1. Sew center back seam, serge and press seam toward left. Sew darts, press toward hem. Sew shoulder and side seams. Serge and press seam toward back.
2. Serge along outer edge of front self-facing. Fold front self-facings onto wrong side, fold again, along marked line. Press edges. Tack facings to neckline edge along neckline marks on front.
3. To finish the neckline; press the bias strip in half along the center. Pin folded bias tape to neckline edges and sew. Trim seam. Press bias tape upwards, fold ends under. Press bias tape onto wrong side and topstitch along folded edge from front of garment.

4. Sew short sides of each flounce. Serge lower edge, press onto wrong side, and topstitch.
5. Sew sleeve seam, serge and press. Pin flounce on sleeve, right sides together, and sew. Serge and press seam allowance toward sleeve. Make a gathering stitch along sleeve cap for ease. Sew sleeve into armhole, matching marks and adjusting ease. Serge seam, press.
6. Serge lower edge of garment, turn onto wrong side, and topstitch.
7. Make buttonholes on right front.
8. Pin right front edge over left front edge, matching front middle lines. On the wrong side of blouse, sew a piece of elastic 12 cm long, along marked line, stretching and topstitching right front on left one. Sew buttons on left.

**TECHNICAL DRAWING:**

