

Sewing Pattern — Jacket 5054

<u>Recommendations on fabric</u>: soft wool or fabrics suitable for costumes

You will also need: 6 buttons

If the pattern has double contour the seam allowances are included. If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

<u>Attention</u>! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

- 1. Center front part 2 details
- 2. Front band 2 details
- 3. Side front part 2 details
- 4. Upper back part 1 folded detail
- 5. Lower back part 1 folded detail
- 6. Collar 2 folded details
- 7. Upper sleeve 2 details
- 8. Lower sleeve 2 details
- 9. Sleeve facing 2 details
- 10. Back neckline facing 1 folded detail

Lining:

- 1. Center front part 2 details
- 2. Side front part 2 details
- 3. Upper back part 1 folded detail
- 4. Lower back part 1 folded detail
- 5. Upper sleeve 2 details
- 6. Lower sleeve 2 details



Fusing:

- 1. Front band 2 details
- 2. Collar 2 folded details
- 3. Sleeve facing 2 details
- 4. Back neckline facing 1 folded detail

INSTRUCTIONS:

- 1. Stitch lower/upper front darts. Stitch lower/upper back darts.
- 2. Stitch side front parts to center front parts.
- 3. Stitch lower back part to upper back part.
- 4. Stitch side/shoulder seams.
- 5. Overstitch the collar neatly along outer contour.

6. Lay front bands on front parts right sides together and topstitch them on front edgings and lapels up to the point of stitching the collar in. Slash seam allowances near this point. Stitch back neckline to front bands' upper ends. Lay collar's open edges between the jacket and front bands with facing (inner collar lays on the jacket.) Stitch outer collar to front bands'/facings' neckline. Stitch inner collar into jacket neckline. Make slashes into roundings. Press seam allowances apart. Fold front bands and facing into wrong side, press edges. Sew collar joining seam's allowances at back neckline (wrong side.)

7. Fold front bands frontward. Fold hem allowances into wrong side up to front edgings, then sew. Fold front bands into wrong side again, sew to hem allowance.

8. Stitch sleeve seams. Stitch sleeve facing seams. Overstitch sleeve hem with sleeve facing. Slash allowances and press them into right side. Stitch sleeves into jacket's armholes. Sew shoulder pads.

9. Stitch seams into lining details. Stitch lining's front edges to front bands right sides together: begin and finish stitching 8 cm before lower edge. Pull the lining into the jacket with its wrong side to jacket's wrong side. Fold lining's open edges under and sew to jacket/sleeve hem allowances. Sew lining's open front edges to front bands.

10. Make buttonholes into right front edging. Sew buttons.



TECHNICAL DRAWING:

