

Sewing Pattern — Waistcoat 5044

Recommendations on fabric: wool/semiwool

You will also need: lining; fusing; 8 buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Middle front part – 2 details
2. Front band – 2 details
3. Side front part – 2 details
4. Middle back part – 2 details
5. Back neckline facing – 1 detail
6. Side back part – 2 details
7. Flap – 4 details

Lining:

1. Middle front part – 2 details
2. Side front part – 2 details
3. Middle back part – 2 details
4. Side back part – 2 details
5. Sacking – 4 details

Fusing:

1. Front band – 2 details
2. Back neckline facing – 1 detail

Additionally: apply the fusing to wrong side of 4 pocket facings (17 cm length and 3.5 cm width each).

INSTRUCTIONS:

1. Apply the fusing to wrong side of pocket entrances.
2. Stitch darts and front relieves.
3. Cut slit pockets with two facings and flaps into front part: lay facings right sides together and topstitch them along joining lines. Cut front part between stitches (stop before ends), diagonally at stitch ends. Do not cut through facing! Press seam allowances apart. Turn facings to wrong side through slit to make a neat frame. Topstitch facing on wrong side along joining seams. Turn small triangle at slit ends into wrong side and stitch on facings between upper stitch ends and lower stitch ends. Lay one soft and one reinforced flaps right sides together and overstitch neatly along outer sides. Turn the flap right sides out, press edges. Set the flap into the pocket on right side, pin the flap under upper facing and topstitch flap on the facing on wrong side. Stitch lining sacking to lower facing, stitch fabric sacking to upper facing. Adjust sackings to make their equal, then stitch.
4. Stitch middle back seam, back relieves, side/shoulder seams.
5. Stitch middle back seam. Stitch front bands to lining front parts; stitch back neckline facing to lining back part. Stitch darts, stitch other seams leaving one of side seams unstitch at 20 cm for turning the waistcoat right side out.
6. Sew the lining/front bands to the waistcoat right sides together.
7. Stitch front edgings up to the seam joining front bands as well as neckline edges.
8. Stitch lining lower edge to hem allowance.
9. Make several slashes into rounded seam allowances. Turn the garment right side out. Sew hem allowance to seam allowances.
10. Pull armholes into right side through the hole into the lining, then stitch right sides inside.
11. Sew lining hole's edges together.
12. Make 8 buttonholes into right front edging. Press edges.

TECHNICAL DRAWING:

