

Sewing Pattern — Blouse 5034

Recommendations on fabric: soft wool jersey

You will also need: 3 small buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

- 1. Front part 1 folded detail
- 2. Back part 1 folded detail
- 3. Front neckline facing 2 details
- 4. Back neckline facing 1 detail
- 5. Sleeve 2 details
- 6. Cuff 2 details
- 7. Inner collar 1 detail
- 8. Outer collar 1 detail

Fusing:

- 1. Back neckline facing 1 detail
- 2. Inner collar 1 detail

INSTRUCTIONS:

- 1. Stitch front darts, press them upward.
- 2. Apply the fusing to wrong side of front closure-placket. Press one-piece closure plackets into wrong side. Lat facings on front part right sides together, topstitch facings along long edges. Cut



placket allowance; slash as a corner at the end. Fold plackets into wrong side, adjust them and topstitch placket's end.

- 3. Stitch shoulder/side seams. Do not catch closure facings!
- 4. Overstitch inner collar with outer one, turn right side out and adjust. Stitch shoulder seams of closure facings and back neckline. Stitch inner collar into neckline. Stitch outer collar into facing neckline. Press seam allowances apart. Sew pressed apart inner collar joining seam/back neckline joining seam allowances together from inside.
- 5. Stitch sleeve seams. Stitch cuffs in rings, press along bendings. Stitch cuffs to sleeves. Stitch sleeves into armholes easing them along sleeve caps.
- 6. Turn in the hem.
- 7. Make buttonholes into right placket, sew buttons to left one.

TECHNICAL DRAWING:

