

## Sewing Pattern — Blouse 5032

Recommendations on fabric: soft fabrics (viscose, silk sateen, crepe)

You will also need: 4 little buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

#### Fabric:

1. Front part – 2 details
2. Front band – 2 details
3. Back part – 1 folded detail
4. Sleeve – 2 details
5. Hem facing – 1 folded detail
6. Collar – 2 folded details
7. Tie – 4 details
8. Cuff – 2 details

Additionally: 2 pipings for sleeves (16 cm length and 2 cm width).

#### Fusing:

1. Front band – 2 details
2. Collar – 1 folded detail
3. Cuff – 2 details

## **INSTRUCTIONS:**

1. Stitch darts and shoulder seams.
2. Cut sleeves as marked. Process slit edges with the piping, width is 0.5 cm. Cut the piping diagonally at slit's top (sleeve's wrong side). Stitch sleeves into armholes.
3. Overstitch 2 ties' long edges. Fold tie's open end under. Tack one tie to left front edging between marks. Tack another tie to right front edge.
4. Cut a braid in 2 equal pieces. Tack one of braids to left front edging's right side.
5. Stitch sleeve/side seams with one stitch catching the tie into left side seam.
6. Stitch inner collar into neckline up to the mark. Stitch outer collar to front bands. Press seam allowances apart, press allowances between shoulder seams toward the collar.
7. Fold hem facing as marked right side out, press along bending line. Stitch outer side to blouse hem, stitch front bands' lower edges to facing's inner long edge. Fold facing's inner side into front bands' right side, lay outer collar on the blouse.
8. Stitch front edgings and collar's outer sides to the mark catching left tie.
9. Fold front bands and facing's inner sides into wrong side; turn the collar right side out. Fold outer collar's lower edge under, stitch outer collar to the joining seam. Sew front bands' upper edges to shoulder seams' allowances. Fold open edge of hem facing's inner side under; pin the facing to joining seam. Stitch the facing to right side along joining seam.
10. Make pleats into sleeve hems laying x on o, then tack them.
11. Fold cuffs along the center, process short edges neatly. Stitch long edge to sleeve hems' right side catching the piping of slit front edge. Fold inner cuff under and stitch to joining seam. Make 2 buttonholes into cuffs at 1 cm from front short edge. Sew another cord to right side seam's allowance at height of left front edge's cord.
12. Fold front edgings into right side as lapels, press slightly.

**TECHNICAL DRAWING:**

