

Sewing Pattern — Waistcoat 5017

Recommendations on fabric: satin or silk

You will also need: fusible interfacing; 4 buttons; lining

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm for all seams

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Center back – cut 2
2. Side back – cut 2
3. Center front – cut 2
4. Side front - cut 2
5. Front band – cut 2
6. Neck facing – cut 1

Lining:

1. Center back – cut 1
2. Side back – cut 2
3. Side front – cut 2

Fusible interfacing:

1. Front band
2. Back neck facing
3. Center front

INSTRUCTIONS:

1. Apply the interfacing to wrong side of front band, back neck facing, center front.
2. Sew side fronts to center fronts and side backs to center backs. Clip into curves and press seams open.
3. Sew center back seam. Press back seam apart.
4. Sew back neck facing to front bands and press seams apart.
5. Sew shoulder seams and press them apart.
6. Pin front band on center front, right sides together. Sew center edge and back neck to facing.
7. Sew lining details leaving side seams unstitched. Press the lining.
8. Pin the lining to the garment, right sides together, and sew to inner edges of front bands and facing, leaving open segments of 10 cm length at bottom as well as to armhole edges. Trim seam allowance close to stitch. Pull front through shoulder slits and turn the garment right side out through one of the open side seams. Sew garment side seam and lining side seams together with one seam at each side.
9. Press garment hem under and sew by hand. Sew front bands to the hem.
10. Make buttonholes on right front and sew buttons on left one.

TECHNICAL DRAWING:

