

## Sewing Pattern — Jacket 5002

Recommendations on fabric: light blouse fabric of natural or mixed fibers.

You will also need: 3-4 buttons

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Fabric:

1. One-piece -belt – 2 pieces
2. Collar – 2 pieces
3. Center back part – 2 pieces
4. Side back part – 2 pieces
5. Side front part – 2 pieces
6. Back neckline facing – 1 folded piece
7. Center front part – 2 pieces
8. Front band – 2 pieces
9. Sleeve – 2 pieces

Fusing:

1. back neckline facing – 1 folded detail
2. front band– 2 details

## **INSTRUCTIONS:**

1. Stitch the one-piece belt along longer sides, then turn it right side out and press. Make a decorative stitch on 0.5 distance from the edge.
2. Sew middle and relief back seams. Insert the one-piece belt into relief seams.
3. Sew front relief seams.
4. Sew shoulder and side seams.
5. Fold front bands and front parts right sides together, then pint them to front bands edges. Overstitch edgings with front bands. Sew front bands shoulder seams and back neckline facing.
6. Trim the collar along the outer contour. Sew the inner collar into neckline, sew outer collar into facing neckline. Press seam allowances apart. Sew inner collar joining seam allowances (ironed apart) and back neckline facings from inside.
7. Trim the hem of the jacket. Sew front bands to hem allowance.
8. Topstitch the jacket along edges and the collar on 0.5 cm distance.
9. Sew sleeves seams. Sew sleeve hems and sew sleeves into armholes, shrinking along the sleeve cap.
10. Tuck buttonholes into the right front part; sew buttons at the left one.
11. Sew shoulder pads.

## **TECHNICAL DRAWING:**

