

Sewing Pattern — Wedding Dress 2010

Recommendations on fabric: lace for bodice; silk sateen, chiffon

You will also need: zipper; 3 decorative flowers; fusing.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 2 cm for back middle seam (to stitch the zipper). 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Sateen:

1. Center back part_3 lower layer – 2 pieces
2. Side back part_3 lower layer – 2 pieces
3. Lower front part_3 lower layer – 1 piece
4. All bodice pieces. Use also as bodice lining

Sheer lace:

1. All bodice pieces

Fusing:

1. All bodice pieces

Chiffon:

1. Two upper layers of front/back parts
2. Lapel along edge – 1 piece
3. Waistband – 3 pieces
4. Shoulder stripes – 2 pieces

INSTRUCTIONS:

1. All front/back part pieces have 3 layers.
2. Stitch all skirt layers along all seams together up to notches at hip level (between upper edge and notches), then layer after layer (to avoid non-aesthetic displacement of transparent chiffon at side seams as well as another seams).
3. The zipper is on middle back seam.
4. Process chiffon lapel/waistband ends at clear edge with en English seams (thin edge seam with closed edge) or with narrow zig zag stitches beginning with notches.
5. Decorate the garment with chiffon roses.

TECHNICAL DRAWING:

