

Sewing Pattern — Wedding Dress 2009

Recommendations on fabric: lace; satin; organza (of two or three tinctures, for example, of lacteous white and cream white as well as light rose), sheer fatin for bodice pieces, ready underskirt

You will also need: zipper, hooks (for neckline closure), lace border for trimming

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 1 cm for middle back seam (to stitch the zipper). 1 cm for other seams

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Satin:

1. Lower back skirt_4 – 2 pieces
2. Lower front skirt_4 – 1 piece

Sheer fatin:

1. All bodice pieces – 3 layers

Sheer lace:

1. All bodice pieces

Organza:

1. 3 upper layers of skirt

Trimming: take lace border of 2 cm width to stitch it (with zig zag stitches) along neckline/front part edges and bodice armholes (you need approximately 3.5-4 m of lace border). In this way you will close front edges of lace.

INSTRUCTIONS:

1. All front upper pieces are of 3 layers of fatin (to make them less transparent and stiff) and of 1 layer of lace.
2. Pleat upper skirts at left side by hand.
3. The zipper is in middle back seam.
4. The skirt has 4 separate layers: 3 upper skirts are of organza, 1 lower is of satin.
5. Make asymmetrical undercut into ready underskirt at hip level, then sew it as lower layer.
6. Sew lace border to neckline/armholes of ready bodice.
7. Overlap the line joining the skirt and the bodice with folded waistband. Sew the waistband to side seams when the garment is on a mannequin.
8. Fix 2 organza flowers on skirt left side.

TECHNICAL DRAWING:

