

## Sewing Pattern — Shirt 6132

Recommendations on fabric: shirt fabric with lycra

You will also need: fusible interfacing; 10 buttons

If the pattern has a double line around it, the seam allowances are included.

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: on side and top edges of sleeve placket — 0.5 cm, along the lower edge – 1.5 cm, all other seams – 1cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

#### Main fabric:

1. Center back - cut 2
2. Side back - cut 2
3. Center front - cut 2
4. Side front — cut 2
5. Placket — cut 2
6. Sleeve placket – cut 2
7. Sleeve – cut 2
8. Collar – cut 2
9. Collar-stand – cut 2
10. Cuff — cut 4

#### Interfacing:

1. Collar – cut 1
2. Collar-stand – cut 1
3. Cuff – cut 2
4. Sleeve Placket – 2 details

## **INSTRUCTIONS:**

1. Apply interfacing to cuff, top collar, inner collar-stand and placket.
2. Sew side fronts to center fronts and side backs to center back. Serge and press the seam towards center. Topstitch edges at 0.5 cm from the seam. Sew center back seam. Serge and press seam toward left. Topstitch at 0.5 cm from the seam.
3. Sew collar, right sides together, along sides, and outer edge. Trim seams. Turn collar out, straighten and press. Topstitch along outer edge and ends of collar. Press lower edge of inner stand-up collar under 1 cm and topstitch at 0.7 cm. Place collar-stand, right sides together, matching upper edge, insert ready-collar between them, match notches and sew, include collar-stand side edges at the same time. Turn ready-collar out and press.
4. Place placket right side onto wrong side of front and sew button stand edge. Turn placket onto right side, turn unsewn edge inside, and topstitch on front part at 0.5 cm from the fold. Topstitch at 0.5 cm off the front band's edge.
5. Sew and serge shoulder edges. Press seam allowance toward back. Topstitch at 0.5 cm from the seam.
6. Sew outer collar-stand with collar into the neckline, press seam toward collar-stand. Topstitch inner collar-stand into connecting seam.
7. Vent: Slit the sleeve according to marked line, trimming the corner in top part of slit. Turn inside section from slit to marked line (that is 1.5 cm), twice at 0.5 cm and topstitch. Fold the placket in half lengthwise, right sides together, and sew corner up to cross notch. Trim off seam allowances close to stitch. Turn placket out, press and sew along fold line from below up to cross notch at 0.1 cm. Place placket and sleeve, right sides together, and sew with inner side on marked line. Trim sleeve across near end of stitch, from the slit up to connecting line. Turn placket to right side, turn inside open edge and Sew. Align placket with marked line on sleeve and topstitch top corner along contour and along cross notch.
8. Sew sleeve into open armhole matching notches and easing along cap. Serge seam and press toward garment.
9. Sew side seam and sleeve seam at the same time. Serge seams and press toward back. Make and baste pleats according to marks.
10. On outer cuff, turn lower edge 1 cm and topstitch at 0.7 cm. Pin cuff, right sides together and sew three sides. Turn cuffs out and press. Sew inner side of cuff to sleeve. Topstitch outer side of cuff into connecting seam.
11. Serge bottom edge of garment, press onto wrong side and topstitch.
12. Make buttonholes on cuffs and on collar-stand and sew buttons. Make buttonholes on right front, sew buttons on left front.

**TECHNICAL DRAWING:**

