

Sewing Pattern — Coat 4169

Recommendations on fabric: thin wool or semiwool fabric

You will also need: soft fusing: 1 button; 1 small button; lining; shoulder pads-raglan.

Seam allowances are provided if the pattern has double contour.

Seam allowances are NOT included if the pattern has single contour and need to be added when laying out and cutting details. 1 cm for all seams, 2 cm for garment hem and sleeve hems, 1.5 cm for front neckline and front middle seam.

Seam allowance: on sleeve hem – 4 cm, other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count double and symmetrical details.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

Main fabric:

1. Collar - 2 details
2. Side back part – 2 details
3. Central back part – 2 details
4. Central front part – 2 details
5. Side front part – 2 details
6. Facing/buttonstand – 2 details
7. Back neckline facing – 1 detail
8. Bottom facing of back part – 1 detail
9. Back part of sleeve – 2 details
10. Front part of sleeve – 2 details
11. Strapping – 1 detail

Lining:

1. Central front part – 2 details
2. Side front part – 2 details
3. Side back part - 2 details
4. Central back part – 2 details
5. Back part of sleeve – 2 details
6. Front part of sleeve – 2 details

Fusing:

1. Central front part – 2 details
2. Facing/buttonstand – 2 details
3. Back neckline facing – 1 detail
4. Upper collar – 1 detail



ATTENTION: Front parts and of back parts of lining are cut excepting the buttonstands width and facings neckline of back part accordingly.

INSTRUCTIONS:

1. Apply fusing to details.
2. Mark darts on front part and on back part. Sew and press darts on back part towards center. Sew bust dart on front part and slash depth. Press apart bust dart.
3. Sew and press apart relief seams on back part and on front part. Sew and press apart middle edge of back part.
4. Stitch back sleeves parts to back part. Stitch sleeves front parts to front parts. Press apart seams.
5. Sew shoulder and top edges of sleeves. Press seams apart. Sew lower edges of sleeves and side edges with one seam. Press seams apart. Sew in shoulder pads.
6. Fold collar details right sides together. Overstitch outer edge of collar, as well as right part end of collar till round mark. Cut seam, slash seam near round mark. Turn and press collar. Stitch decorative stitch along seam on 1 cm off the edge. Sew collar in the neckline. Press seam.
7. Sew and press apart shoulder edges facings neckline of back part and facings/buttonstands. Stitch the facing hem of back part to buttonstand. Press seams apart.
8. Sew seams and sew in sleeves on lining details, leaving a slit in left lower seam of sleeve to be turned out later. Stitch lining to inner facing/buttonstand edges and facings.
9. Put facing/buttonstand with facing onto right side of front part right side downwards, pin together and overstitch facing/buttonstand, right lapel, the neckline of front part, the neckline of back part and jacket's hem. Stitch round from sides of front part. Topstitch seam allowance of stand on buttonstand. Put the stitch on 0, 2 cm off the seam.
10. Press hem of sleeve. Stitch lining to the sleeve edge. Turn jacket onto right side. Sew work slit.
11. Stitch decorative stitch along facing/buttonstand of right lapel and hem of the garment on 1 cm off edge.
12. Make buttonhole on front parts according to button position, sew a decorative button on left part. Sew a small button on wrong side of right front part.
13. Fold strapping in half lengthwise and overstitch long edge. Turn the detail and press. Topstitch strapping according to markers on right part of front part. Run through the end of collar.

TECHNICAL DRAWING:

