

Sewing Pattern — Trousers 6110

Recommendations on fabric: whipcord;

You will also need: lining; fusing; elastic braid of 4.5 cm width for waistband; elastic cord for trousers hem; 4 metal clocks; cord for waistband; trimming cord.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 4.5 cm for hems, 0 cm for lining edge (lining reaches garment's hem).

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.

CUTTING:

(On the pattern pieces, "beam" means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Front part – 2 pieces
2. back part – 2 pieces
3. Front insert – 2 pieces
4. Back insert – 2 pieces
5. Waistband – 1 piece
6. Sacking – 4 pieces
7. Side part – 2 pieces

Cut bias 2 fabric stripes of 3.5 cm width for trimming. Stripes' length depend on trimming's length. NB! After trimming is ready, there must remain seam allowance of 1 cm. Otherwise, one must regulate width of cut stripes self.

Lining:

8. Front part – 2 pieces
9. Back part – 2 pieces



INSTRUCTIONS:

1. Reinforce pocket entrance at sacking. Stitch sackings along pocket entrance and turn into right side. Topstitch pocket entrance. Lay sackings on side part along coincidence line and stitch all details to front part. Topstitch the seam.
2. Stitch stripes together, press seams. Fold ready stripe along the center, insert the cord and make a stitch along cord's contour.
3. Stitch side inserts to front/back parts inserting trimming. Stitch side seams, then topstitch. Stitch middle seams, topstitch along left part.
4. Mark lines of topstitching the elastic braid at waistband. Pierce 2 holes (at 8 cm distance) for cord between topstitchings at front part's middle seam level. Stitch separately waistband and elastic braid in ring. Insert elastic braid into waistband, stretch the braid to waistband's length and make 2 decorative stitches. Stitch the waistband to trousers catching elastic braid.
5. Stitch lining's side seams and middle seam. Stitch the lining to garment's waistband.
6. Set blocks into hems. Press hems first at 1 cm, then 3.5 cm under.
7. Stitch fabric/lining inside leg seams.
8. Topstitch hems.
9. Press ready trousers.
10. Pull cords into trouser hems.

TECHNICAL DRAWING: