

Sewing Pattern — Shorts 6109

Recommendations on fabric: whipcord;

You will also need: fusing; elastic braid of 4.5 cm for waistband; cord for waistband.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Seam allowance: 1 cm for all seams, 4.5 cm for garment hems.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Left front part – 1 piece
2. Left small insert – 1 piece
3. Left large insert – 1 piece
4. Left lower part – 1 piece
5. Right front part – 1 piece
6. Right small insert – 1 piece
7. Right large insert – 1 piece
8. Right side part – 1 piece
9. Back part – 2 pieces
10. Waistband – 1 piece
11. Sacking – 4 pieces

INSTRUCTIONS:

1. Stitch right/left front parts separately. Press seams.
2. Stitch sackings to back part and front parts according to marks. Slash allowances at pocket entrance's marks. Turn sackings right side out, press and topstitch. Stitch sackings. Stitch side seams. Make fixings at pocket entrance.

3. Press hems first at 1 cm, then 3.5 cm under. Stitch front seams and back middle seams. Topstitch along left part. Stitch inside leg seams.

4. Mark lines of topstitching the elastic braid at waistband. Pierce 2 holes (at 8 cm distance) for cord between topstitchings at front part's middle seam level. Stitch separately waistband and elastic braid in ring. Insert elastic braid into waistband, stretch the braid to waistband's length and make 2 decorative stitches. Stitch the waistband to trousers catching elastic braid.

5. Topstitch hem allowances.

6. Press ready shorts.

7. Pull the cord into the waistband.

TECHNICAL DRAWING:

