

Sewing Pattern — Sweatshirt 6104

Recommendations on fabric: fleece, stretch-knit

You will also need: cord for collar

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: 1 cm for all seams; 2 cm for lower sleeve hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Advice:

Knit fabric pieces are sewn together with special stretch-stitch or narrow zig-zag stitch. Seam allowance on hem is stitched with twin needles to save stretchiness. Pieces can also be sewn together with 3 or 4 – thread serger. When serging, cut seam allowances to 0.6 – 0.8 cm.

Fabric 1:

Center front - cut 1
Center back - cut 1
Upper sleeve - cut 2
Collar - cut 1

Note: Knits have different amounts of stretch so make sure that the sewn collar is wide enough for the head to fit through the opening before sewing it to garment.

Fabric 2:

Upper front inset - cut 1
Upper back inset - cut 1
Lower front inset - cut 1
Lower back inset - cut 1
Upper sleeve inset - cut 2
Lower sleeve - cut 2



Fabric 3:

Middle front inset - cut 2

Middle back inset - cut 2

Middle sleeve inset - cut 2

INSTRUCTIONS:

1. Sew upper front inset to center front, middle front inset to upper front inset, and lower front inset to middle front inset. Repeat for the back. Serge seams and press upward. Topstitch at .5 cm from seams.
2. Sew shoulder seams. Serge and press toward back.
3. Make buttonholes according to marks in collar. Sew collar into a ring, and press along center. Sew collar equally around neckline, stretching slightly. Topstitch under buttonholes along top of collar to form a casing for cord.
4. Sew upper sleeve inset to upper sleeve, middle sleeve inset to upper sleeve inset, and lower sleeve to middle sleeve inset. Serge and press seams. Topstitch at .5 cm from seams. Sew sleeves into open armholes. Serge and press seam toward garment. Topstitch on garment at .5 cm from seam.
5. Sew side seams from slit mark, and sleeve seams with one stitch. Serge and press.
6. Serge lower edge of sleeves, turn seam allowance onto wrong side and topstitch.
7. Serge lower edge of front and back. Turn seam allowance and slit edge seam allowance onto wrong side, and topstitch.

TECHNICAL DRAWING: