

Sewing Pattern — Shirt 6096

NB! 0.8 cm seam allowances are already in patterns.

Recommendations on fabric: mixed fabric.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Back part – 1 folded piece
2. Back yoke – 1 piece
3. Left front yoke – 1 piece
4. Left front part – 1 piece
5. Right front yoke – 1 piece
6. Right front part – 1 piece
7. Placket – 1 piece
8. Front sleeve – 2 pieces
9. Back sleeve – 2 pieces
10. Stand-up collar – 2 folded pieces
11. Inner collar fall – 1 folded piece
12. Outer collar fall – 1 folded piece
13. Pocket – 2 pieces
14. Pocket placket – 2 pieces
15. Pocket facing – 2 pieces
16. Flap – 4 pieces
17. Loop epaulette – 4 pieces
18. Front waistband – 2 folded piece
19. Back waistband – 1 folded piece

APPEARANCE:

Uniform shirt for men, with buttoned center closure; left front part: stitched placket; front/back parts: yokes. Front parts: two upper pockets with buttoned flaps. Set-in two-seamed short sleeves with one-piece cuffs. Turn-down collar with stand-up detail; loop epaulettes are on shoulders. Garment hem with stitched waistband is gathered with elastic braid at sides.

TECHNICAL DRAWING:

