

Sewing Pattern — Shirt 6094

NB! 0.8 cm seam allowances are already in patterns.

Recommendations on fabric: mixed fabric.

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

(On the pattern pieces, “beam” means straight of grain. Lay out your pieces accordingly. Some pieces will be cut on the fold. This is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.)

Main fabric:

1. Collar – 2 folded pieces
2. Yoke – 2 folded pieces
3. Patch pocket – 2 pieces
4. Patch pocket flap – 4 pieces
5. Loop – 1 piece
6. Front part – 2 pieces
7. Inset pocket sacking – 2 pieces
8. Inset pocket valance – 2 pieces
9. Inset pocket off-set welt – 2 pieces
10. Front band – 2 pieces
11. Epaulette – 2 folded pieces
12. Upper sleeve – 2 pieces
13. Lower sleeve – 2 pieces
14. Back part – 1 folded piece
15. Cuff – 4 pieces
16. Foot loop – 2 pieces

APPEARANCE:

Uniform shirt for men, with buttoned front closure. Back part: yoke and two soft pleats to ease movements. Front parts: two upper pockets with buttoned flaps. Front bands: slit pockets with off-set welts. Set-in two-seamed sleeves with buttoned cuffs. Turn-down collar with one-piece stand-up detail. Shoulders with epaulettes.

TECHNICAL DRAWING:

