

Sewing Pattern — Shirt 6060

Recommendations on fabric: artificial silk of 150 cm width

You will also need: fusing; 9 buttons

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Collar – 2 folded pieces
2. Stand-up collar – 2 folded pieces
3. Back yoke – 2 folded pieces
4. Back part – 1 folded piece
5. Front part one-piece with front band – 2 pieces
6. Sleeve – 2 pieces
7. Belt loop – 4 pieces

Fusing: one-piece front band, collar, stand-up collar

INSTRUCTIONS:

1. Apply the fusing to wrong side of one-piece front band, collar, stand-up collar.
2. Press one-piece front bands to wrong side, fold inner edges under and topstitch.

3. Lay yoke details right sides together, insert back part detail and stitch. Fold yoke upwards, tack along edges and process as one detail.
4. Sew side/shoulder edges. Fold the hem to wrong side, fold it under and topstitch.
5. Lay collar both details right side together and stitch along outer contour. Turn right side out, press and topstitch. Lay stand-up both details right sides together, insert the collar between upper edges and continue stitching along closure projections. Press stand-up open edges in, insert neckline edge between them and stitch along edge.
6. Lay loop details in pairs right side together and overstretch along three edges. Turn belt loops to right side, neaten, fold open edges under and topstitch along edge. Topstitch loops on sleeve wrong side according to marks.
7. Sew sleeve seams and sew sleeves into armholes. Press sleeve hem to wrong side, fold it under and topstitch.
8. Make buttonholes into left front part, loops and stand-ups. Sew buttons on right front part and sleeves.

TECHNICAL DRAWING:

