

Sewing Pattern — Shirt 6047

Recommendations on fabric: flax of 150 cm width

You will also need: fusing; 4 buttons

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Center back part – 1 folded piece
2. Side back part – 2 pieces
3. Side front part – 2 pieces
4. Collar – 2 folded pieces
5. Stand-up collar – 2 folded pieces
6. Front part (one-piece with front band) – 2 pieces
7. Back neckline facing – 2 pieces
8. Front armhole facing – 2 pieces

Fusing: one-piece front bands, collar, stand-up collar, front/back armhole facings

INSTRUCTIONS:

1. Apply the fusing to wrong side of one-piece front bands, collar, stand-up collar, front/back armhole facings.
2. Sew side back parts to center one. Sew center front part to side ones.
3. Press one-piece front bands to wrong side, fold the front band edge under and topstitch.

4. Sew side/shoulder seams, press allowance backwards and topstitch.
5. Sew collar both details along outer contour right sides together. Turn right side out, press and topstitch. Lay both stand-ups right sides together, insert the collar between upper edges along marking and stitch (continue stitching on closure projection). Press stand-up open edges in, insert neckline between them and sew along the edge.
6. Sew facing in ring and sew them to armholes right sides together. Turn facings to wrong side, neaten them, press and topstitch.
7. Press garment hem to wrong side, fold it under and topstitch.
8. Make buttonholes into left front part, and sew buttons on right one.

TECHNICAL DRAWING:

