

Sewing Pattern — Waistcoat 6007

Recommendations on fabric: dense wool/semiwool/cotton velvet/cloth.

You will also need: artificial fur of 90 cm length and 140 cm width; lining of 30 cm length and 140 cm width; trimming of 480cm length and 2 cm width; separating zip (length depends on your size).

If the pattern has double contour the seam allowances are included.

If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out and cutting details.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Back part – 1 folded piece
2. Front part – 2 pieces
3. Pocket – 2 pieces

Use to cut the lining:

4. Back/front parts without change
5. Pocket excluding upper allowance

NB: if you have check fabric, take into account when pinning patterns on the fabric how checks will coincide along seams

INSTRUCTIONS:

1. Lay the pocket on the lining right sides together, coincide edges and make double decorative stitch along pocket entrance. Make another double stitch 4 cm lower than the first one.
2. Press pocket's open edges and topstitch the pocket along marking with double stitch.
3. Tack fabric back part on fur back part wrong sides together along all edges.

4. Lay the piping on the garment right sides together, coincide along edges, and stitch at the distance of $\frac{1}{4}$ of piping width. Round garment's edge with the piping, fold the rest of piping ($\frac{1}{4}$ of piping width) and topstitch along the bending coinciding with the seam stitches before.
5. Do the same for fur front edging.
6. Press fabric front edgings' allowances into wrong side, lay the zipper on wrong side, coincide teeth with front edging's bending, and topstitch at 1.5 cm distance.
7. Lay fabric front part on fur front part right sides together and stitch along hems; turn right side out and make 1 cm decorative topstitching. Tack fabric front part and fur front part along side edges, armholes and shoulders.
8. Sew fur front edgings to the zipper with blind stitches.
9. Stitch shoulder/side seams, trim allowances with the piping as describes above. Do the same for neckline and armholes.

TECHNICAL DRAWING:

