

Sewing Pattern — Jacket 4155

Recommendations on fabric: natural or mixed silk costume fabrics

You will also need: fusing; lining; hook with eyelet; shoulder pads; sleeve heads

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: all seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Middle part of front part – 2 details
5. Lower front part – 2 details
6. Panel of front part – 2 details
7. Back neckline facing – 2 details
8. Bottom facing of back part – 1 detail
9. Bottom facing of front part – 2 details
10. Buttonstand – 2 details
11. Upper sleeve part – 2 details
12. Lower sleeve part – 2 details
13. Cuff – 2 details

Lining:

1. Central back part – 2 details
2. Side back part – 2 details
3. Side front part – 2 details
4. Middle part of front part – 2 details
5. Upper sleeve part – 2 details
6. Lower sleeve part – 2 details

Lining details are cut on main patterns excluding the width of front and back parts hem facing

Fusing:

1. Lower front part – 2 details
2. Panel of front part – 2 details
3. Back neckline facing – 1 detail
4. Buttonstand – 2 details
5. Cuff – 2 details
6. Bottom facing of back part – 1 detail
7. Bottom facing of front part – 2 details

INSTRUCTIONS:

1. Apply fusing to corresponding details .
2. Sew darts on back part, press depths towards center. Sew relieve seams on back part, press seam allowances apart. Sew middle edge of back part, press seam allowances apart. Stitch back neckline facing to back part, slash seam allowances, press onto the facing.
3. Fold lower part of front part with panel and overstitch buttonstand edge and lower edge between round markers. Slash seam allowances in corners, turn detail onto right side, press.
4. Fold buttonstand with panel and overstitch buttonstand edge leaving 3-4 cm to top edge and inserting hook and eyelet according to markers. Slash seam allowances in corners.
5. Stitch middle part of front part to panel on vertical edge, press seam onto panel. Make plaits on lower part according to drawing, fix them on top edge. Stitch lower edge of middle front part to lower part, and lower edge of buttonstands to panel. Press the seam upwards.
6. Sew relieve edges of front part, press seam allowances towards center.
7. Sew and press apart shoulder and side edges.
8. Sew elbow sleeve seam. Press seam allowances on lower part. Sew and press apart front sleeve seam.
9. Fold cuff in half lengthwise right sides together and overstitch corners from fold up to marker. Fold cuff into the ring and sew sections from edge up to marker, press seam allowances apart. Stitch outer side of cuff to lower edge of sleeve, press seam onto sleeve.
10. Sew sleeves into armholes according to notches, gathering the rounding into top part. Sew in shoulder pads and sleeve heads.
11. Sew and press apart shoulder edges of back part and buttonstand neckline facings. Sew and press apart side edges of the back and front parts hem facing.
12. Sew seams on lining details and sew in sleeves, leaving a slit for turning out in left elbow seam of sleeve. Stitch lining to inner buttonstand edges and facings.
13. Turn buttonstand with facing onto right side and overstitch open section of front part neckline, back part neckline and jacket hem. Overstitch from side of front part.
14. Stitch lining to inner edge of cuff. Turn jacket through slit in sleeve. Sew slit in sleeve.

TECHNICAL DRAWING:

