

Sewing Pattern — Coat 7207

Coat for a girl, full height 122-160 cm, bust girth 60-88 cm.

Recommendations on fabric: soft fabric suitable for coat

You will also need: fusing; lining; 9 buttons of 3 cm in diameter and 5 buttons of 1.5 - 2 cm in diameter

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: hem and lower edge of sleeve – 3.5 cm, all other seams - 1 cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Main fabric:

1. Central upper back part – 2 details
2. Central lower back part – 2 details
3. Side upper back part – 2 details
4. Side lower back part – 2 details
5. Back yoke - 1 detail
6. Back inset – 1 detail
7. Side upper front part – 2 details
8. Side lower front part – 2 details
9. Central upper front part – 2 details
10. Central lower front part – 2 details
11. Front yoke - 2 details
12. Front inset – 2 details
13. Central part of the hood – 1 detail
14. Side part of the hood – 2 details
15. Collar – 2 details
16. Flap – 2 details
17. Pocket – 2 details
18. Buttonstand – 2 details
19. Back neckline facing – 1 detail

20. Upper sleeve part – 2 details
21. Lower sleeve part – 2 details
22. Facing of front inset – 1 detail
23. Belt loop – 1 detail
24. Hood facing – 1 detail

Lining:

1. Central back part – 2 details
2. Side back part - 2 details
3. Side front part – 2 details
4. Flap –2 details
5. Pocket – 2 details
6. Upper sleeve part – 2 details
7. Lower sleeve part – 2 details

Fusing:

1. Buttonstand – 2 details
2. Back neckline facing – 1 detail
3. Central upper front part – 2 details
4. Central lower front part – 2 details
5. Front yoke – 2 details
6. Front inset – 2 details
7. Flap – 2 details
8. Upper collar – 2 details
9. Front inset facing – 1 detail
10. Hood facing – 1 detail

Also apply fusing to: armhole of side front part, armhole of side back part; hem seam allowances of: lower part of sleeve, upper part of sleeve, central back part, side back part, side front part.

INSTRUCTIONS:

Attention: Put decorative stitch at 0.8 cm off the edge along seams and along the perimeter of pockets and flaps.

1. Apply fusing to details.
2. Sew details of upper back part. Press seams to center edge and stitch. Sew details of lower back part. Press seams to center edge and stitch. Sew center edges of back part details. Press seams apart.
3. Stitch back inset to upper and lower details. Press seams onto inset and stitch. Stitch back yoke to back part. Press seams onto yoke and stitch.
4. Sew details of upper front part. Press seams towards center of front part and stitch. Sew details of lower front part. Press seams towards center of front part and stitch.
5. Stitch front inset to upper and lower details exactly up to marker. Cut the inset on left front part flush with the line of buttonstand. Slash seam allowance on right front part only on inset near notches. Press seams onto inset and stitch only up to marker. Overstitch loose end of the inset with facing. Overstitch exactly from the notch up to the notch. Turn details out and press. Stitch front yoke to front part. Press seams onto yoke and stitch.
6. Sew shoulder and side edges. Press seams apart.
7. Overstitch the pocket with lining, leaving a slit in upper edge to turn it out later. Slash seam allowances on rounded parts, turn the pocket out and press. Sew the slit. Topstitch the pocket according to markers.
8. Fold flaps with lining right sides together and overstitch on three sides. Cut seam allowances,

turn out and stitch. Serge a buttonhole on the flap and cut it through. Topstitch the flap onto the coat.

9. Sew upper collar into the neckline of the coat. Press seams apart.

10. Sew and press apart shoulder edges of back part / buttonstand neckline facing. Press seams apart. Stitch lower collar to buttonstand and facing. Press seams apart.

11. Fold buttonstands with the garment, turning loose end of the inset onto right side of front part. Overstitch edges of front bands and of collar with one seam. Slash seam allowances in corners, turn garment right side out, press. Stitch loose end of front inset. Fix allowances of collar connecting seams close to seams.

12. Serge belt loop detail on the one long side. Press seam allowances onto the belt loop and topstitch (serged seam allowance is on top). Make several belt loops. Stitch belt loops to the coat according to technical drawing.

13. Sew, press and stitch elbow sleeve seam. Press lower edge of sleeve. Sew front sleeve seam. Sew sleeves into armholes according to notches, easing in on rounded part. Press seam allowances towards back part and front part. Stitch the seam of the armhole along back and front yokes.

14. Sew seams and sew in sleeves on lining details, leaving a slit in right front seam of sleeve.

15. Press hem of the garment. Sew lining to inner facing/buttonstand edges. Sew lining to hem of the coat. Turn garment through the slit in sleeve. Sew the slit in sleeve. Put decorative stitch along front band and collar.

16. Sew details of the hood. Press seams apart. Sew lining details of the hood, press seams to central part. Sew the hood facing to lining. Press seams towards facing. Overstitch the hood on all sides, leaving a slit near lower edge of central part. Turn the hood out, press and stitch. Make buttonholes on the hood.

17. Serge buttonholes on right front part. Sew buttons on pockets, upper collar and left front part according to buttonholes.

TECHNICAL DRAWING:

