

Sewing Pattern — Dress 7206

Recommendations on fabric: thick silk fabrics suitable for dresses (silk, viscose, polyester); chiffon or organza

You will also need: blind zipper, elastic yarn, bias tape, atlas tape for the belt.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: on hem of the garment – 0. 5 cm, all other seams – 1cm

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Silk:

1. Back part - 2 details
2. Front part - 1 detail
3. Sleeve – 4 details
4. Underskirt, front part – 1 folded detail
5. Underskirt, back part – 2 details

Chiffon:

1. Underskirt, front part – 1 folded detail
2. Underskirt, back part – 2 details
3. Overskirt, front part – 1 folded detail
4. Overskirt, back part – 2 details

INSTRUCTIONS:

1. Fold sleeve details pairwise right sides together and overstretch along the lower edge. Press the seam. Lay the details out. Stitch the elastic yarn along the seam, placing elastic on lining side.
2. Stitch sleeves to back part and front part. Press seam towards side of sleeve. Sew side seams, serge seams and press to back part. Overstretch armhole with bias tape.
3. Sew side edges on details of the skirt. Serge seams and press to back part. Serge middle back edge separately and sew from hem up to marker. Topstitch seam allowances along slit on chiffon details.
4. Lay details of the skirt as follows: lower layer — silk, then chiffon underskirt and then — chiffon overskirt. Fix details of the skirt on waist line and then sew as one-layer detail. Stitch loosely along waist line on skirt and gather ruffles. Stitch skirt to bodice. Serge and press upwards.
5. Sew zipper into middle seam, without catching chiffon details. Fold the bias tape in half lengthwise wrong sides together and press. Fold the bias tape from right side with neckline edge and overstretch. Slash seam. Turn bias tape onto wrong side and topstitch along the fold. Turn ends of bias tape inside and fasten.
6. Overstretch hem of skirts with rolled seam, slightly stretching the edge.
7. Turn atlas tape edges twice on 0.7 cm and topstitch. Cut the tape into 2 parts and topstitch at side seam level. Decorate front part of the dress with silk or organza flowers.

TECHNICAL DRAWING:

