

Sewing Pattern —Skirt 7200

Recommendations on fabric: natural or mixed suiting fabric.

You will also need: fusible interfacing, invisible zipper, elastic of 2 cm wide, decorative belt of 2 cm wide with buckle.

Seam allowances: hem of dress – 1.5 cm, other seams – 1 cm.

Note on seam allowances:

- If the pattern has double contour the seam allowances are included. They are 1 cm unless specified otherwise.
- If the pattern has single contour, the seam allowances are NOT included and need to be added when laying out the pattern.

Note on length of fabric:

Attention! The amount of fabric needed for your pattern is not included. It will depend on the selected pattern size, the width, and design of the fabric you plan to use. First, print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm). Measure how much fabric you will need. Don't forget to account for pieces that need to be cut multiple times and pieces that are cut on the fold.



CUTTING:

Main fabric 1:

1. Back – cut 1
2. Front – cut 1
3. Waistband - cut 1

INSTRUCTIONS:

1. Make pleats on front. Fold edges are directed toward center. Topstitch pleats according to technical drawing.
2. Sew left side seam inserting decorative belt. Press and serge seam. Serge right side edges. Sew right side seam from mark down to hem. Press seam open. Sew in zipper.

3. Apply fusible interfacing to waistband. Press belt in half lengthwise right side inwards. Sew outer part of waistband to upper edge of the skirt, stitching the corners of waistband. Attach elastic to back part of waistband at side seams level. Turn inner edge of waistband inwards and topstitch into waistband connecting seam.
4. Press hem to wrong side, serge and topstitch.
5. Sew second end of the belt onto first pleat at 2 cm from the fold according to technical drawing.

TECHNICAL DRAWING:

