

Sewing Pattern — Baby nest 7145

Note: nest patterns come “to grow into”.

Recommendations on fabric: natural fabrics

You will also need: lining; zipper (length is shown on front pattern piece, depending on the height); decorative cord; 2 caps for cord; elastic of 2.5 cm wide.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: all seams – 1 cm, outer edge of hood – 3 cm; neckline, lower edge of hood – 0.7 cm.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Front – cut 2
2. Back – cut 1
3. Cuff – cut 2
4. Side hood – cut 2
5. Central hood – cut 1

Lining:

1. Front – cut 2
2. Back – cut 1
3. Side hood – cut 2
4. Central hood – cut 1

INSTRUCTIONS:

1. Sew zipper to front bands.
2. Sew side hood to central hood. Mark location of holes and serge holes for cord on hood.
3. Sew central and side hoods from lining.

4. Place lining and main fabric of hood right sides together and stitch outer edge. Turn hood right side out and press. Make a decorative stitch at 2 cm from the edge.
5. Place front and back right sides together and sew shoulder edges, lower edges of sleeves, side edges and bottom (without catching the zipper).
6. Sew cuff into ring, leaving an opening for elastic. Fold cuff in half lengthwise right side out. Sew cuff to sleeve.
7. Sew hood into neckline.
8. Sew seams on lining, leaving an opening in side seam.
9. Place lining and main fabric right sides together and stitch on front band, neckline and hem of sleeve. Turn nest right side out through the opening and sew the opening closed.
10. Set the elastic into opening in cuff and fasten it. Make a stitch along front band at 0.5 cm from zipper. Cut holes on hood, set the cord and put caps.

TECHNICAL DRAWING:

