

## Sewing Pattern — Top 7104

Recommendations on fabric: denim

You will also need: fusible interfacing; clasp; eyelets; studs

**Note:** By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: all seams – 1 cm, 2 cm for garment hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



### **CUTTING:**

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

#### Main fabric:

1. Center front – cut 2
2. Middle front – cut 2
3. Side front – cut 2
4. Center back – cut 2
5. Side back – cut 2
6. Front strap – cut 4
7. Strap – cut 4
8. Flap – cut 4
9. Upper band/facing – cut 2

Interfacing: flaps; self-facing front bands.

### **INSTRUCTIONS:**

1. Apply the interfacing to wrong side of flaps and self-facing front bands.
2. Sew center front t to middle front, right sides together. Press seams towards the center and topstitch. Sew side front to middle front, right sides together. Press seams toward the center and topstitch.
3. Sew center back seam, press toward left and topstitch. Sew center back to side back, right sides together. Press seams toward the center and topstitch.
4. Sew side seams. Press seams toward back and topstitch.
5. Sew flaps, right sides together along three sides. Turn flap right side out. Trim corners. Topstitch along outside edge at 0.1 cm and 0.5 cm from edge.
6. Sew straps, right sides together, along long sides. Turn the strap right side out, trim corners. Topstitch strap's outer edges at 0.1 cm and 0.5 cm from edge. Make eyelets into straps.
7. Sew front straps, right sides together, along long sides. Turn front strap right side out, trim corners. Topstitch at 0.1 cm and 0.5 cm from three edges. Turn front strap's upper part onto wrong side, inserting the clasp. Topstitch with triple stitch.
8. Sew upper band/facing, right sides together, along three edges inserting the strap and strap's upper part. Turn right side out, trim corners.
9. Apply the fusing to wrong side of self-facing front bands. Serge top's lower edge and front bands. Fold front band onto right side, sew lower corner, trim and turn it right side out. Understitch. Press onto wrong side, Topstitch.
10. Sew right side of inner edge of upper band/ facing to garment's wrong side top edge. Fold outer band/facing edge under, and topstitch along the seam, inserting flaps at marked position..
11. Press the bottom edge onto wrong side, and topstitch.

### **TECHNICAL DRAWING:**

