

Sewing Pattern — Skirt 7088

Recommendations on fabric: denim

You will also need: fusible interfacing; 1 zipper; 1 button

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: 1 cm for all seams, 2 cm for hem

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Waistband – 1 piece
2. Left front part – 1 piece
3. Right front part – 1 piece
4. Side front panel – 2 pieces
5. Center back panel – 2 pieces
6. Side back panel – 2 pieces
7. Belt loop – 1 piece
8. Button catch – 1 piece
9. Side pocket – 2 pieces
10. Side pocket – 4 pieces
11. Pocket side part – 2 pieces

Interfacing: flap, waistband, button catch

INSTRUCTIONS:

1. Apply interfacing to wrong side of flap, waistband, button catch.
2. Lay flap details right sides together and overstitch along outer contour. Turn the flap right side out through upper open edge. Make decorative stitch at 0.5 cm from flap edge.
3. Stitch side seams of side front/side back parts and neaten them. Press the seam backwards.
4. Mark pocket place on side part. Press inverted pleat into pocket. Neaten pocket upper edge, fold it under and topstitch. Stitch front pocket side part to pocket. Neaten joining seam. Trim pocket side part upper edge, fold it under and topstitch at 1 cm from edge. Stitch pocket side part to skirt side part.
5. Stitch front/back relieve seams so that pocket side part enters the relieve seam. Neaten relieve seams and press it towards front/back panels center. Make decorative stitch at 0.5 cm from relieve seam. Fix side part and the pocket with vertical stitch.
6. Mark pocket place on front part. Topstitch pocket according to marks. Fold the flap into right side and topstitch it at 0.5 cm from topstitching.
7. Stitch back panel middle edge. Neaten back panel middle seam and press it.
8. Neaten front panel middle edge. Stitch front panel middle edge between closure notch and hem and press the seam.
9. Press one-piece closure facing into wrong side. Stitch the zipper under closure allowance (left edge). Stitch zipper free braid to right one-piece facing. Fold button catch along the center and overstitch it along two sides. Turn button catch right side out and press it, neaten button catch side edge. Stitch button catch to closure left allowance. Topstitch slit right edge (catch facing).
10. Fold belt loop along the center wrong side out, adjust edges and overstitch at 0.5-0.7 cm from edges. Then turn it right side out, placing the seam or making an edging of 0.1-0.2-cm width into wrong side, and press.
11. Press the waistband along the center right side out. Neaten waistband lower edge. Cut elastic braid according to size and topstitch on waistband at two sides (from front/back belt loops level). Cut belt loops according to size and topstitch them on waistband on marking. Stitch waistband raw edge to garment. Overstitch waistband ends. Slash extra fabric and turn ends right side out. Topstitch neaten edge on seam joining the waistband. Topstitch belt loops on waistband upper edge.
12. Neaten garment hem, fold in into wrong side and topstitch. Make buttonhole into waistband. Sew the button.

TECHNICAL DRAWING:

