

Sewing Pattern — Skirt 7077

Recommendations on fabric: velour/denim

You will also need: fusible interfacing; zipper.

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: 1 cm for all seams.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. First flounce – 1 piece
2. Second flounce – 1 piece
3. Third flounce – 1 piece
4. Fourth flounce – 1 piece
5. Waistband – 1 piece

Interfacing: waistband.

INSTRUCTIONS:

1. Apply interfacing to wrong side of waistband.
2. Make easy-stitched seam along upper edges of the first, second, third and for the flounces at 0.5 cm from edges. Pull detail upper edge according to previous detail's length lower edge, adjusting pleats along the length.
3. Stitch the first flounce to the second one. Neaten joining seam and press it. Stitch the third flounce to the second one. Neaten joining seam and press it. Stitch the fourth flounce to the third one. Neaten joining seam and press it.

4. Press the waistband along the center right side out and neaten lower inner edge.
5. Neaten garment side edges. Stitch side seam up to closure notch. Press side seam apart pressing zipper slit. Stitch the zipper into side seam. Stitch the waistband to skirt upper edge. Overstitch waistband ends, cut seam allowances in corners and turn it right side out. Topstitch lower neaten edge of waistband on joining seam and press ready waistband.
6. Neaten skirt hem. Press hem allowance into wrong side and topstitch.

TECHNICAL DRAWING:

