

Sewing Pattern — Wide Trousers 7075

Recommendations on fabric: cotton velvet.

You will also need: iron-on interfacing; elastic braid; lining.

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowance: 1 cm for all seams, 1.5 cm for hem, 3 cm for side pocket upper edge.

Attention! First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



CUTTING:

Fabric:

1. Side pocket – 1 piece
2. Front – 2 pieces
3. Back – 2 pieces
4. Waistband – 1 piece
5. Side – 2 pieces
6. Side front – 2 pieces
7. Side back – 2 pieces
8. Lower part – 2 pieces

Lining:

9. Pocket underlining – 2 pieces

Interfacing: waistband.

INSTRUCTIONS:

1. Apply the interfacing to the wrong side of the waistband.
2. Stitch the side pocket darts. Press them towards the pocket center. Neaten the pocket edges. Press the pocket upper edge under and topstitch it. Press the pocket along the contour according to the pattern.

3. Stitch the side front piece to the front piece stop stitching 5 cm before the end. Neaten the seam. With right sides together overstretch the front pocket entrance with the pocket underlining. Push the underlining through the opening and make decorative stitch along the pocket entrance 0.5 cm in. Pin the front piece to the marks of the side front pocket entrance. Stitch the pocket underlining and neaten the seam. Fix the side front piece to the front piece along the upper/side edges with 1-cm stitch.
4. Stitch the side back piece to the front piece. Neaten the joining seam and press it backwards. Stitch the lower piece to the side back/front pieces. Neaten the joining seams and topstitch them.
5. Neaten the centre edges of the front/back pieces. Stitch the front seam and neaten it. Stitch the centre back pieces to the side back pieces. Neaten the seams and press them towards the sides.
6. Topstitch the pocket to the garment 0.2 cm in from the edges fixing it at the corners.
7. Stitch the inside leg seams and neaten them, press them backwards. Stitch the crotch edges. Make another stitch along this seam.
8. Press the waistband along the center right side out and neaten one lower edge. Stitch the waistband side edges and press the seam open. Stitch the waistband to the garment. Topstitch the neaten edge on the seam joining the waistband, leaving a slit for elastic braid. Pull the braid into the waistband and fix the braid side edges together.
9. Neaten the hems and stitch the elastic braid to the side seams. Fold the hems to the wrong side and topstitch 1.5 cm from the edge.

TECHNICAL DRAWING:

