

Sewing Pattern — Jacket 4143

Recommendations on fabric: flax, linen, or other natural or mixed suiting fabric

You will also need: fusible interfacing, lining, 7 buttons, shoulder pads, sleeve heads

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowance; hem – 4 cm; all other seams -1 cm

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches. They must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Darts: The fold of the dart is always pressed toward the center of your garment, or down toward the hem.

Main fabric:

1. Upper back – cut 1 on fold
2. Back waistband – cut 1
3. Lower back – cut 1
4. Upper front – cut 2
5. Front waistband – cut 2
6. Lower front – cut 2
7. Upper sleeve - cut 2
8. Lower sleeve - cut 2
9. Back neck facing – cut 1
10. Front facing – cut 2
11. Sleeve strap – cut -cut 2
12. Back belts - cut 2
13. Pocket flap – cut 4
14. Pocket – cut 2
15. Pocket facing – cut 2
16. Upper sleeve facing – cut 2
17. Lower sleeve facing – cut 2

Lining:

1. Pocket lining –cut 2
2. All other pieces are cut from lining using main pattern pieces, excluding the width of back neck facing and front facing.

Fusible interfacing:

1. Back neck facing – cut 1
2. Front facing –cut 2
3. Sleeve strap – cut 2
4. Back belts - cut 2
5. Pocket flap – cut 2
6. Upper sleeve facing – cut 2
7. Lower sleeve facing – cut 2

INSTRUCTIONS:

1. Apply fusible interfacing listed pieces.
2. Sew darts on upper back, press towards center. Make and fasten pleat on upper back. Sew back waistband to upper back, press seam toward waistband. Sew lower back to waistband, press seam toward waistband. Make a decorative stitch along the waistband at 0.5 cm from the seam.
3. Pin flaps right sides together, and sew outer edge. Trim corners, and turn right side out. Straighten seams and press. Make buttonhole.
4. Make and fasten pleat on pocket. Sew the pocket facing to lining, leaving a slit for turning out. Press the seam upwards. Pin pocket and lining right sides together and sew outer edges. Trim corners, turn pocket right side out, straighten and press. Make a decorative stitch 3 cm from the upper edge.
5. Sew darts on upper front, press towards center. Sew front waistband to upper front, snip seam allowance near marker and press toward waistband. Sew lower front to waistband, inserting pocket flap, trim seam allowance on waistband near marker and press seam toward waistband. (right side will extend out for buttonhole closure)
6. Turn flap upwards and topstitch pocket onto lower front. Sew buttons onto pockets according to buttonholes.
7. Pin front facing to center front, right sides together, and sew to within 2-3 cm of neckline. Sew lower corner, trim corners. Understitch, and turn facing onto wrong side, straighten seam, press.
8. Turn front facing out, and make a decorative stitch 0.5 cm along the upper edge of the waistband up to marker. Stop stitching, turn facing onto wrong side and make decorative stitch on the waistband extended section up to lower marker. Stop stitching again, and continue decorative stitch along lower edge of the waistband from marker to side seam.
9. Fold back belts in half lengthwise, right sides together, and sew curved and long sides. Trim corners and turn right side out. Straighten seams and press. Make decorative stitch along the contour 0.5 cm from the edge. Make buttonholes.
10. Sew and press apart shoulder seams. Sew side seams, inserting back belts. Press seam apart. Sew buttons onto belts, fastening them to garment.
11. Sew and press apart shoulder seams of back neck facing front facings. Sew facing to neckline, right sides together. Clip into curves, understitch and turn onto wrong side, straighten seams, and press.
12. Fold sleeve strap in half lengthwise, right sides together, and sew curved and long side. Trim corners and turn right side out. Straighten seams and press. Make a decorative stitch along the outer edge at 0.5 cm off the edge. Make buttonhole.

13. Sew sleeve seam from top to lower marker, inserting strap. Press seam allowances onto lower part. Sew and press apart front sleeve seam.
14. Sew front edge of sleeve facing. Pin facing to sleeve, right sides together, and sew hem and slit in sleeve seam. Trim corners, turn the facing onto wrong side, straighten, press.
15. Make a gathering stitch along sleeve cap. Sew sleeves into armhole according to notches, easing in cap. Sew in shoulder pads and sleeve heads.
16. Sew lining same as main fabric, leaving a slit in front right seam of sleeve for turning.
17. Sew lining to inner edges of facings.
18. Sew lining to sleeve hems and garment hem. Turn the jacket right side out through the slit in sleeve. Sew slit. Make a decorative stitch 0.5 cm from the edge along the neckline and center fronts.
19. Make buttonhole on right waistband extension, sew button on left. Sew buttons onto sleeves.

TECHNICAL DRAWING:

