

## Sewing Pattern — Skirt 7073

Recommendations on fabric: denim

You will also need: fusing; zipper

If the pattern has double contour the seam allowances are included.

Seam allowances are NOT included by default and need to be added when laying out and cutting details if your pattern has single contour.

Seam allowances: 1 cm for all seams

**Attention!** First of all please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to count pair parts and symmetrical parts.

When sewing the garment, pay attention to notches, they must coincide.



### **CUTTING:**

Main fabric:

1. Right front panel – 1 piece
2. Left front panel – 1 piece
3. Back panel – 2 pieces
4. Large back flounce – 1 piece
5. Small back flounce – 1 piece
6. Large right front flounce – 1 piece
7. Small right front flounce – 1 piece
8. Large left front flounce – 1 piece
9. Small left front flounce – 1 piece
10. Front facing – 1 piece
11. Back facing – 2 pieces

Fusing: front/back facings.

### **INSTRUCTIONS:**

1. Apply the fusing to wrong side of front/back facings.
2. Neaten middle back edge. Stitch middle edge leaving closure slit. Stitch the slit in.

3. Neaten all flounces' lower edges, press into wrong side and topstitch them.
4. Lay small back flounce wrong side on large back right side and fix along upper edge. Stitch flounces to back panel right sides together. Neaten the seam and press it towards panel. Make decorative stitch along joining seam.
5. Lay small left front flounce wrong side on large left front flounce right side and fix them together along upper edge. Stitch flounces to left front panel right sides together. Neaten the seam and press it towards panel. Make decorative stitch along joining seam.
6. Lay small right front flounce wrong side on large right front flounce right side and fix them together along upper edge. Stitch flounces to right front panel right sides together.
7. Lay left front panel on right front panel right sides together, folding flounces out, and stitch them on the seam joining flounces. Neaten the seam and press it rightwards. Make decorative stitch along joining seam.
8. Neaten side edges of front/back panels. Stitch garment side seams and press them apart.
9. Stitch facings side edges and press seams apart. Neaten facing outer edges.
10. Neaten front/back panel upper edge with facing. Topstitch oversteitching allowance on facing at 0.2 cm from oversteitching. Fold facing side edges under and sew by hand.

**TECHNICAL DRAWING:**

