

Sewing Pattern — Skirt 7072

Recommendations on fabric: denim

You will also need: fusible interfacing; zipper; button

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam allowances: 1 cm for all seams, 2 cm for hem.

Attention! First of all, please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need. Don't forget to take into account pieces to be duplicated or cut on a fold.

When sewing the garment, pay attention to notches, they must match up with corresponding pieces.



CUTTING:

The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Main fabric:

1. Waistband – 1 piece
2. Left front part – 1 piece
3. Right front part – 1 piece
4. Front yoke – 1 piece
5. Right back part – 1 piece
6. Left back part – 1 piece
7. Back yoke – 1 piece
8. Belt loop – 1 piece

Interfacing: waistband.

INSTRUCTIONS:

1. Apply interfacing to wrong side of waistband.
2. Stitch front yoke to left front part. Neaten joining seam, press it and make decorative stitch.
3. Stitch right front part to front panel. Neaten joining seam, press it and make decorative stitch.

4. Stitch back yoke to left back part. Neaten joining seam, press it and make decorative stitch.
5. Stitch right back part to back panel. Neaten joining seam, press it and make decorative stitch.
6. Neaten garment side edges. Stitch side seams leaving closure slit into left side seam as well as hem slits. Press side seams apart pressing hem slits and closure slit.
7. Fold the belt loop along the center wrong side out, adjust edges and overstretch it at 0.5-0.7 cm from edges. Then turn it right side out, placing seam at fold line or making an edging of 0.1-0.2 cm width into wrong side, and press it.
8. Press the waistband along the center right side out and neaten waistband lower inner edge. Cut belt loops according to size and topstitch them on marking on waistband lower edge.
9. Stitch the zipper into left side seam. Stitch the waistband with belt loops to skirt upper edge. Overstretch waistband ends, cut corner allowances and turn it right side out. Topstitch waistband lower neaten edge on joining seam and press ready waistband. Topstitch belt loops on waistband.
10. Neaten garment hem. Press hem allowance into wrong side and topstitch it. Make decorative stitch along slits 0.5 cm from slit edges.

TECHNICAL DRAWING:

